

Grupo 108



PASSENGER CARS TIRES

Grupo 108

Business Promoter in Latin America

www.grupo108.com

info@grupo108.com

EL SALVADOR

Grupo 108 Centroamerica SA de CV
Ciudad Satelite, pasaje Aries, polígono
M, casa No. 23, San Salvador,
El Salvador

INDIA

Grupo108 Business Services Pvt. Ltd.
Villa No. 328, Omaxe City II, Mangliya,
Indore, Madhya Pradesh, Pin - 453771
India,



Uni-directional tread pattern provides high speed performance. Better Mileage and quiet Ride.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
225/35ZR20	90W	8J	340	600	666	230
245/35ZR20	95W	8J	340	690	680	248
255/35ZR20	97W	9J	340	730	686	260
265/35VR22	102V	9J	340	850	745	271
305/40VR22	114V	11J	340	1080	803	313
305/45VR22	118V	11J	340	1080	833	313
305/35VR24	112V	11J	350	1120	824	313

TIRES





High Comfortable on travel, Good handling,
Low noise emission.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
ST175/80R13-6PR	91Q	5 B	350	615	610	177
ST205/75R14-6PR	100Q	5 J	350	800	664	203
ST205/75R15-6PR	101Q	5 J	350	825	689	203
ST205/75R15-8PR	107Q	5 J	450	975	689	203
ST215/75R14-6PR	102Q	6 J	350	850	678	216
ST225/75R15-8PR	113Q	6 J	450	1150	719	223
ST235/80R16-10PR	123Q	6 J	550	1550	782	235

TIRES





Suite to all weather condition, Low rolling resistance.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
195R14C-6PR	104N	5 J	350	805/770	666	198
195R14C-8PR	106N	5 J	450	935/890	666	198



Excellent anti-irregular wear performance & high mileage, Low resistance to rolling, Lower noise emission, Excellent heat radiation & guiding stability.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
7.00R16LT-12PR	115/110N	5 F	670	970/920	775	200
6.50R15LT-10PR	107/105N	5 F	550	970/920	730	180



Three center grooves improve drainage at high speed. Block tread design provides better cornering and low noise. Superior Handling Capacity.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
195/70R15C-6PR	104/102S	6J	303	730	655	201





Better drainage grooves disperse water at high speed. Easy Cornering and Skid Prevention.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
215/75R15	100S	6 J	260	800	703	216
225/75R15	102S	6 J	260	850	719	223
235/75R15	105S	6 J	240	920	733	235





Wider Tread, Even Wear, Higher mileage, all weather application, excellent performance on ice or rough road. Better traction for smooth and quiet ride.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
6.50R16LT-10PR	107/103N	5 F	560	975/860	750	185





Wider Tread, Even Wear, Higher mileage, all weather application, excellent performance on ice or rough road. Better traction for smooth and quiet ride.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
LT215/85R16	115/112Q	6J	550	1215/1120	772	216
LT225/75R16	115/112Q	6J	550	1215/1120	744	223
LT235/75R15	104/101Q	6 J	350	900/825	745	249
LT235/85R16	120/116Q	6 J	550	1380/1260	806	235
LT245/75R16	120/116Q	7 J	550	1380/1260	774	248
LT265/75R16	123/120Q	7 J	550	1550/1440	804	267

TIRES





All weather application, excellent performance on ice or rough road. Better traction for smooth and quiet ride.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
P255/70R16	109S	7 J	241	1030	764	260
P265/70R16	111S	8 J	241	1090	778	267
P265/70R17	113S	8 J	241	1150	804	267
P265/75R16	114S	7 J	241	1180	804	267
P245/65R17	105S	4 J	241	924	750	248
P235/75R15	105S	6 J	241	920	745	249
P245/75R16	109S	7 J	241	1030	774	248

TIRES





Suite to all weather condition, Low rolling resistance

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
185R14C	102/100N	5 J	450	840/800	651	188





Superior Tread compound provides excellent performance on dry and wet road.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
175/70R13	82T	5.00B	250	475	576	177
185/60R14	82H	5 J	250	475	578	189
185/65R14	86H	5 J	250	530	596	189

TIRES





Tread design provide excellent high speed performance and great traction. High lateral Skid prevention ability. Highly comfortable, low noise emission, low fuel consumption

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
155/65R13	73H	4 J	250	365	532	157
175/70R13	82T	5.00B	250	475	576	177
185/70R13	86T	5 J	250	530	590	189
185/60R14	82H	5 J	250	475	578	189
195/60R14	86H	6 J	250	530	590	201
175/65R14	82H	5 J	250	475	584	177
185/65R14	86H	5 J	250	530	596	189
195/65R14	89H	6 J	250	580	620	201
185/70R14	88T	5 J	250	560	624	186
195/70R14	91T	6 J	250	615	636	197
205/70R14	98T	6 J	250	750	644	209
195/55R15	85V	6 J	250	515	595	201
185/60R15	84H	5 J	250	500	603	189
195/60R15	88V	6 J	250	560	615	201
205/60R15	91V	6 J	250	615	627	209
185/65R15	86H	5 J	250	560	621	189





Tread design provide excellent high speed performance and great traction. High lateral Skid prevention ability. Highly comfortable, low noise emission, low fuel consumption

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
195/65R15	91V/91H	6 J	250	690/615	635	201
205/65R15	94V/94H	6 J	250	670	647	209
215/65R15	100H/96H	6 J	250	800	673	230
205/70R15	96T	6 J	250	710	681	209
215/70R15	98H/98T	6 J	250	750	695	221
225/70R15	100T	6 J	250	800	709	228
235/70R15	103T	7 J	250	875	725	240
205/55R16	91W	6 J	300	615	632	214
215/55R16	97V/93H	7 J	350	730	642	226
225/55R16	99V/95H	7 J	340/250	775/690	654	233
205/60R16	92V/92H	6 J	250	630	662	209
215/60R16	95H	6 J	300	690	664	221
225/60R16	98V/98H	6 J	250	750	686	228
235/60R16	100V/100H	7 J	250	800	700	240
215/65R16	98H	6 J	250	750	698	221





Uni-directional tread pattern provides super high speed performance. Opti-Noise Technology for a quiet ride. Big angle block tread design provides better cornering. Enhanced performance with comfortable rides.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
205/40ZR17XL	84W	7 J	290	500	596	212
215/45ZR17XL	91W	7J	290	615	626	213
225/45ZR17XL	94W	7 J	290	670	634	225
215/35ZR18XL	84W	7 J	290	500	607	218
225/40ZR18XL	92W	8J	290	630	637	230
235/40ZR18XL	95W	8 J	290	690	645	241
245/40ZR18XL	97W	8 J	290	730	653	248
235/35ZR19XL	91W	8 J	290	615	647	241
245/35ZR19XL	93W	8 J	290	650	655	248

TIRES





Asymmetric Tread Pattern. Superior Tread compound provides excellent performance on dry and wet road. Suitable for V-Speed rating and Higher.

Tyre Size	Load Index & Speed Rating	Rim Size	Inflation Pressure (kpa)	Max Load (Kg)	Overall Diameter (mm)	Section Width (mm)
6.50R16LT-10PR	107/103N	5 F	560	975/860	750	185
185/55R14	80V	5 J	300	440	556	189
195/50R15	82V	6J	290	475	576	201
185/55R15	82V	5 J	300	475	586	189
195/55R15	85V	6J	250	515	595	201
205/55R16	91W	6 J	300	615	632	214
215/45ZR17XL	91W	7J	290	615	626	213
225/45ZR17	94W	7 J	290	670	634	225
225/40ZR18XL	92W	8J	290	630	637	230

TIRES

